

## Machinery Specification

### Bronx Slitting Line

UNCOILER (MASTER COIL)		RECOILER (SLIT COIL)	
Inside Diameter	508mm, 610mm	Inside Diameter	508mm, 610mm
Max Outside Diameter	1850mm	Max Outside Diameter	1850mm
Max Width	1850mm	Min/Max Width	30mm - 1850mm
Max Weight	28 tonnes	Max Weight	28 tonnes

	Min	Max
Thickness Range	0.25	3.0mm

### Bronx Multi-Strand Blanking Line

UNCOILER (MASTER COIL)		BLANK SPECIFICATION	
Inside Diameter	610mm	Length	420mm - 5500mm
Max Outside Diameter	1850mm	Width	Min 195mm
Max Width	1515mm	Thickness Range	0.35mm-3.0mm
Max Weight	23 tonnes	Tolerances	+/- 0.40mm

### Weybridge Slitting Line

UNCOILER (MASTER COIL)		RECOILER (SLIT COIL)	
Inside Diameter	457mm, 508mm, 610mm	Inside Diameter	457mm, 508mm, 610mm
Max Outside Diameter	1800mm	Max Outside Diameter	1650mm
Max Width	1000mm	Min/Max Width	19mm - 1000mm
Max Weight	12 tonnes	Max Weight	12 tonnes

	Min	Max
Thickness Range	0.4mm	2.0mm

### Narrow Blanking Line

UNCOILER (MASTER COIL)		BLANK SPECIFICATION	
Inside Diameter	508mm, 610mm	Length	195mm - 1500mm
Max Outside Diameter	1850mm	Width	195mm - 650mm
Max Width	650mm	Thickness Range	0.40mm-3.0mm
Max Weight	5 tonnes	Tolerances	+/- 0.40mm